

Product Specifications

Applications – This product can be applied to most smooth surfaces. Commonly used for floor-applications but can be used on glass, metal, PVC, dry erase boards, desk tops and other work surfaces.

Product Variations – This material can be printed on with high quality waxed based inks formulated for vinyl. Consult your ink supplier before printing and test all ink prior to use.

Application Temperature	Minimum application temperature in +6 degrees C (+40F)
Color Fade	Up to 5 years under normal exposure conditions Performance can vary depending upon U.V. exposure
Water Resistance	Test for specific application
Humidity Resistance	Good
Storage Stability	1-year shelf life when stored at 21 degrees C (70F) and 50% relative humidity

Installation

1. Wash surface to be striped to eliminate dust, dirt and oil residue. Water-based cleaners are recommended. Avoid using oil based cleaners as they may leave a film and prevent the adhesive from adhering to the contact surface.
2. Remove backing and apply to surface with pressure for maximum adhesion.
3. Cut material to desired length.

A wider width clear Floor-Mark can be applied over the top for increased durability in high traffic areas.



Colors	520 Green	537 Tomato Red	545 Brown		
	524 Daffodil	542 Black	560 Purple		
	533 Olympic Blue	543 White	562 Pink		
	534 Royal Blue	544 Orange	530 Clear		
Widths	25.4mm (1")	50.8mm (2")	76.2mm (3")	101.6mm (4")	127mm (5") (clear only)

Warranty

Floor-Mark is distributed with the intent that this product will be useful, but without any warranty. It is provided "As Is" without warranty of any kind, either expressed or implied, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. The entire risk as to the quality and performance of the product is with the end-user.